






Intertek

4010143

MODEL: LIA

U.S. ENVIRONMENTAL PROTECTION
AGENCY CERTIFIED TO COMPLY WITH
2020 PARTICULATE EMISSION
STANDARDS

LISTED PELLET FUEL BURNING ROOM HEATER, ALSO FOR USE IN MOBILE HOMES. TESTED TO: ASTM
E1509-12 / ULC S627-00 / ASTM E2515-11 / ASTM E2779-10



A : 0 (0 mm)

B : 4 (102 mm)

INSTALL AND USE ONLY IN ACCORDANCE WITH MANUFACTURER'S INSTALLATION AND OPERATING INSTRUCTIONS. CONTACT LOCAL BUILDING AND FIRE OFFICIALS ABOUT RESTRICTIONS AND INSTALLATION INSPECTION IN YOUR AREA.

WARNING: DO NOT INSTALL APPLIANCE IN A SLEEPING ROOM IN A MOBILE HOME.

FOR USE WITH: WOOD PELLETS (ONLY)

USE OF OTHER FUEL MAY DAMAGE UNIT AND CAUSE A HAZARDOUS CONDITION.

DO NOT CONNECT THIS UNIT TO A CHIMNEY SERVING ANOTHER APPLIANCE.

FREESTANDING INSTALLATION: IN ACCORDANCE WITH MANUFACTURE'S INSTALLATION, INSTALL ON A NON COMBUSTIBLE FLOOR PROTECTION WHICH EXTENDS UNDER THE PRODUCT, AND 6" (153 mm) TO THE FRONT AND 6" (153 mm) EACH SIDE OF THE FUEL OPENING. **ALCOVE INSTALLATION:** THE CLEARANCE TO THE TOP OF THE UNIT IS 59" (150 cm) MEASURED FROM THE FLOOR. SEE MANUAL FOR ADDITIONAL INSTRUCTION.

VENTING SYSTEM: A TYPE "PL" OR "L" VENTING SYSTEM MUST BE USED. CLEARANCES FROM VENT ARE AS PER VENT MANUFACTURERS INSTRUCTIONS. SEE LOCAL BUILDING CODE, APPLIANCE AND VENT MANUFACTURERS INSTRUCTIONS FOR PRECAUTIONS REQUIRED FOR PASSING THROUGH A COMBUSTIBLE WALL OR CEILING. INSPECT AND CLEAN VENTING SYSTEM FREQUENTLY. UNDER CERTAIN CONDITIONS OF USE THE VENT SYSTEM MAY PLUG RAPIDLY.

OPERATE ONLY WITH THE DOORS (FIRE DOOR AND FUEL HOPPER LID) FULLY CLOSED. REPLACE GLASS WITH CERAMIC GLASS ONLY.

CAUTION: MOVING PARTS MAY CAUSE INJURY.

WARNING: HOT PARTS. DO NOT OPERATE WITH PANELS OPEN.

ROUTE POWER SUPPLY CORD AWAY FROM UNIT. DANGER: RISK OF ELECTRIC SHOCK.

DISCONNECT POWER BEFORE SERVICING UNIT.

MODEL POWER RATING: 120 V AC; 1.39 A; 60 Hz (3.07 A WITH IGNITER)

BURN RATE (DRY) : 1.26 - 4.35 lb/hr **INPUT :** 10827 - 37258 Btu/hr

EMISSION VALUE : 0.700 g/hr

CERTIFICATION TEST EMISSIONE VALUE, TEST METHOD AND STANDARD MET WITH 2020 PELLET.

THIS WOOD HEATER NEEDS PERIODIC INSPECTION AND REPAIR FOR PROPER OPERATION. CONSULT THE OWNER'S MANUAL FOR FURTHER INFORMATION. IT IS AGAINST FEDERAL REGULATIONS TO OPERATE THIS WOOD HEATER IN A MANNER INCONSISTENT WITH THE OPERATING INSTRUCTIONS IN THE OWNER'S MANUAL.

MANUFACTURED BY:

DATE OF MANUFACTURE: 07/2016

GRUPPO PIAZZETTA

Via Montello, 22 - 31011 Casella d'Asolo (TV) - Italy

DISTRIBUTED BY:

Pacific Energy

Fireplace Products Ltd.