



Intertek

4001506

MODEL: P158 D




U.S. ENVIROMENTAL PROTECTION AGENCY
CERTIFIED TO COMPLY WITH 2020
PARTICULATE EMISSION STANDARDS USING
PELLET FUEL

REFER TO THE INTERTEK DIRECTORY OF BUILDING PRODUCTS
([HTTPS://BPDIRECTORY.INTERTEK.COM](https://bpdirectory.intertek.com)) FOR DETAILED INFORMATION.

LISTED PELLET FUEL BURNING ROOM HEATER, ALSO FOR USE IN MOBILE HOMES.

CERTIFIED TO :

ASTM E1509-12 / ULC S627-20 / ASTM E2515-17 / ASTM E2779-17 / CSA B415.1-10



H05026550 / 10

A : 2 1/4" (57 mm)

B : 7" (178 mm)

F : 3" (76 mm)

INSTALL AND USE ONLY IN ACCORDANCE WITH MANUFACTURER'S INSTALLATION AND OPERATING INSTRUCTIONS. CONTACT LOCAL BUILDING AND FIRE OFFICIALS ABOUT RESTRICTIONS AND INSTALLATION INSPECTION IN YOUR AREA.

WARNING: DO NOT INSTALL APPLIANCE IN A SLEEPING ROOM.

FOR USE WITH: WOOD PELLETS ONLY

USE OF OTHER FUEL MAY DAMAGE UNIT AND CAUSE A HAZARDOUS CONDITION.

DO NOT CONNECT THIS UNIT TO A CHIMNEY SERVING ANOTHER APPLIANCE.

VENTING SYSTEM: A 3" OR 4" DIAMETER TYPE "PL" OR "L" VENTING SYSTEM MUST BE USED. CLEARANCES FROM VENT ARE AS PER VENT MANUFACTURER'S INSTRUCTIONS. SEE LOCAL BUILDING CODE, APPLIANCE AND VENT MANUFACTURER'S INSTRUCTIONS FOR PRECAUTIONS REQUIRED FOR PASSING THROUGH A COMBUSTIBLE WALL OR CEILING. INSPECT AND CLEAN VENTING SYSTEM FREQUENTLY. UNDER CERTAIN CONDITIONS OF USE THE VENT SYSTEM MAY PLUG RAPIDLY.

FREESTANDING INSTALLATION: IN ACCORDANCE WITH MANUFACTURE'S INSTALLATION. INSTALL ON A NON COMBUSTIBLE FLOOR PROTECTION WHICH EXTENDS AT LEAST UNDER THE PRODUCT, AND A MINIMUM OF 6" (152 mm) IN FRONT OF UNIT AND BEYOND EACH SIDE OF THE FUEL LOADING AND ASH REMOVAL OPENING. THE FLOOR PROTECTION IS REQUIRED UNDER ANY HORIZONTAL VENTING.

OPERATE ONLY WITH THE DOORS (FIRE DOOR AND FUEL HOPPER LID) TIGHTLY CLOSED DURING OPERATION. REPLACE GLASS ONLY WITH CERAMIC GLASS. ORIGINAL SPARE PARTS AVAILABLE FROM YOUR DEALER.

CAUTION: MOVING PARTS MAY CAUSE INJURY.

WARNING: HOT PARTS. DO NOT OPERATE WITH PANELS OPEN.

ROUTE POWER SUPPLY CORD AWAY FROM UNIT. DANGER: RISK OF ELECTRIC SHOCK.

DISCONNECT POWER BEFORE SERVICING UNIT.

ELECTRICAL RATING: 115/120 VAC; 60 Hz; 1.9 A (OPERATION); 3.5 A (IGNITION PHASE)

BURN RATE (DRY) : 1.84 - 4.73 lb/hr

HEAT INPUT : 15015 - 38600 Btu/hr

PARTICULATE EMISSION RATE : 0.793 g/hr

HEAT OUTPUT : 12482 - 31491 Btu/hr

THIS WOOD HEATER NEEDS PERIODIC INSPECTION AND REPAIR FOR PROPER OPERATION. CONSULT THE OWNER'S MANUAL FOR FURTHER INFORMATION. IT IS AGAINST FEDERAL REGULATIONS TO OPERATE THIS WOOD HEATER IN A MANNER INCONSISTENT WITH THE OPERATING INSTRUCTIONS IN THE OWNER'S MANUAL.

MANUFACTURED BY:

DATE OF MANUFACTURE: 11/2021

PIAZZETTA

Via Montello, 22 - 31011 Asolo (TV) - Italy